

JUNIPER

OBEETEE®
S P H - W O O L S



SMOKE GREY



DARK GREY



Z. BLACK



INDIGO BLUE



RED



REGAL RED



BURGUNDY



RUSSET



MONTE BROWN




SPRING GREEN



WEED GREEN

LISAN

OBEETEE®
CARPETS



SILVER GREY



SLATE GREY



ULTRAMARINE



CARMINE



RUBBY RED



WINE RED



CORAL



SALMON



MAPLE



LAWN GREEN



CACTUS GREEN

OBEETEE®

TEXTILES

SPECIFICATIONS

Weight (gm/m ²)	: 700
Nominal Thickness (mm)	: 4.00
Width (Mtr.)	: 1.83 & 3.05
Roll Length (Mtr.)	: 40-45
Weight & Thickness measurement tolerance	: ± 10%
Width measurement tolerance	: ± 1.5%

JUNIPER

Colour Fastness	
Wash (IS 11969)	: 5
Light (IS 6686)	: 4
Compressional Recovery	
Instantaneous	: 85%
After one hour	: 92%
Flammability Test (IS 5641)	: Passes the test

PERFORMANCE

Durability	
Loss of fibre after 1000 cycles	: 0.30%

SPECIFICATIONS

Weight (gm/m ²)	: 900
Nominal Thickness (mm)	: 5.0
Width (Mtr.)	: 2.0 & 3.05
Roll Length (Mtr.)	: 40-45
Weight & Thickness measurement tolerance	: ± 10%
Width measurement tolerance	: ± 1.5%

LISAN

Colour Fastness	
Wash (IS 11969)	: 5
Light (IS 6686)	: 4
Compressional Recovery	
Instantaneous	: 85%
After one hour	: 92%
Flammability Test (IS 5641)	: Passes the test

PERFORMANCE

Durability	
Loss of fibre after 1000 cycles	: 0.15%

THE PRODUCT

The OBEETEE range of carpets sets high standards in quality, durability and decor. Manufactured in a state of the art, imported plant, Obetee non woven carpets meet international standards of fibre bonding & stain resistance, thermal insulation and antistatic properties. These carpets offer unique features like unilayer formation for excellent fibre bonding & processing for very high resistance to abrasion. These are available in a wide range of assorted shades. Every OBEETEE product is produced for an addition to our extensive stock range or one-off carpet to meet customer's individual needs. No wonder Obetee offers best value for money.

INSTALLATION

For best results, installation of carpets should be done by a professional. Carpets should always be laid on an surface which is clean and dry to ensure long life. Stretch the carpet fully and apply the adhesive evenly throughout, during installation. Adhesive, evenly spread, on the entire carpet is recommended. Overlap the edges of the carpets to be joined and then splice to achieve a perfect joint.

MAINTENANCE

Though carpet brush can be used, use of vacuum cleaner is recommended. Prompt stain removal is important. For liquid, use blotting paper or absorbent cloth. Use shampoo or non alkaline liquid detergent for removing water based stains. Semi solids and greasy substances should be scraped out with the help of a knife cleaned with cleaning solvents.

SHADE VARIANCE

Due to inherent limitation of dyeing techniques, colours may vary slightly from lot to lot. Use carpet rolls from the same lot in one area.

Specifications are subject to change due to technical improvements.

OBEETEE TEXTILES PVT. LTD.

1011-B, 10th Floor, Indra Prakash Building
21, Barakhamba Road, New Delhi-110001 (India)
Phone : 011-23354260, Telefax : 23354261
E-Mail : oti.delhi@obeteetee.com
www.obeteetee.com



VRS COMMERCIALS

A UNIT OF VRS GROUP



CONTACT US :



vrscommercials@vrsgroup.in



+91 9957212265



www.vrsCommercials.com